

SmartReader Plus 10

Product Specifications

Type: Four-Channel Temperature
RTD

GENERAL SPECIFICATIONS

Size: 107 mm x 74 mm x 22 mm (4.2" x 2.9" x 0.9")
Weight: 110 grams (3.75 ounces)
Case Material: Noryl® plastic
Battery: 3.6 volt Lithium
Resolution: 12-bit (1 part in 4096)
Mounting: Magnetic backing or locking eyelet
Clock Accuracy: +/- 2 seconds per day
Sampling Methods: Continuous (First-in, First-out)*, Stop When Full (Fill-then-stop)
**Not available with sample rates faster than eight seconds*
Operating Limits: -40 to 70°C (-40 to 158°F) and 0 to 95% RH (non-condensing)
PC Requirements: IBM PC or 100% compatible with at least one free serial port, 2 MB of RAM memory, and 2 MB of hard disk space
Software Requirements: TrendReader® Standard 2 (compatible with Windows® 2000, and XP)

Memory Size: 128KB (capable of storing up to 87,000 readings)
Sampling Rates: User selectable rates from 25 per second to once every eight hours (BP-101 battery pack or PS-201 power supply required for sampling rates faster than eight seconds)
Number of Channels: Four (one internal thermistor channel for ambient temperature and three external channels for use with RTD* temperature probes)
**Any RTD with a Temperature Coefficient of Resistance (TCR) of 0.00385 can be used*

SENSOR SPECIFICATIONS

RTD Channels - The following specifications are for:

- 4-Wire Platinum 100 Ohm @ 0° C & TCR = 0.00385
- 4-Wire Platinum 1000 Ohm @ 0° C & TCR = 0.00385

Temperature

Range: -230 to 300°C (-382 to 572°F)
Accuracy: +/- 0.3°C (+/- 0.54°F) + resolution or +/- 0.06% full scale (of logger)
Resolution: +/- 0.14°C (+/- 0.25°F)

Resistance (100 Ohm)

Range: 5 to 210 Ohm
Accuracy: +/- 0.13 Ohm, +/- 0.06 % full scale
Resolution: +/- 0.05 Ohm

Resistance (1000 Ohm)

Range: 50 to 2100 Ohm
Accuracy: +/- 1.3 Ohm, +/- 0.06% full scale
Resolution: +/- 0.5 Ohm

Logger is Temperature compensated by internal temperature sensor for the range of -20 to 80°C (-4 to 176°F)

The SmartReader Plus 10 is a powerful and accurate RTD temperature logger designed for easy monitoring and recording of temperature. Any RTD probe or sensor with a TCR of 0.00385 can be used with this logger.



WARRANTY

Internal Battery: 10 Years
Data Logger: 3 Years

APPLICATIONS

Food process verification,
 pharmaceutical storage monitoring,
 transportation of temperature-sensitive goods, etc.

Model#: SRP-010-128K
Cat#: 01-0132